

# **Curbstone Paint WB**

# **Product Description**

Curbstone Paint WB is water-based coating that provides a protection layer for external cement surfaces and curbs, produced to resist weather and available in many colors.

## **Features and benefits**

- Suitable for all asphalt surfaces.
- Very high adhesion power.
- High abrasion resistance.
- Durable.
- Weather resistant.

## **Typical use**

- Used as an exterior coating is suitable for use on all types of road surfaces asphalt.
- concrete or brick surfaces.

## **Substrate**

Road surfaces asphalt, brick surfaces, concrete.

# **Product Data**

| Packaging size   | 3.2 Litr.              |
|------------------|------------------------|
| Glossy           | Matt                   |
| Color            | Yellow, white, Black   |
| Solids by Volume | 38 ± 2%                |
| Density          | 1.50 g/cm <sup>3</sup> |
| VOC              | 27 g/l                 |

# **Application data**

#### The product can be applied by

Spray Recommended

Roller Recommended

Date of issue:12.08.2017



#### Brush

Recommended for stripe coating and small areas. Care must be taken to achieve the specified dry film thickness.

#### **Cleaning of painting tools**

Once mixing is complete, tools should be cleaned immediately after use with clean thinner.

#### Film Thickness per coat

| Dry film thickness         | 90 µm -    | 180 µm   |
|----------------------------|------------|----------|
| Theoretical spreading rate | 4.2 m²/l - | 2.1 m²/l |

Thinner (solvent to mix with)

Water.

#### **Dilution (Mix Ratio)**

Maximum 10%.

#### **Conditions during application**

Do not apply if the temperature is below 10°C and not more than 40°C.

| Drying and curing time | 25 °C        |
|------------------------|--------------|
| Surface (touch) dry    | 30 – 40 min. |
| Full Cure              | 6 hrs.       |

### **Directions for use**

#### Surface preparation

- Ensure that surface is thoroughly cleaned and free from grease, oil, dirt, salt and other containment.
- Surface must be dry.

#### **Recommended Paint System**

#### Number of coats:

Two coats, additional coats might be needed depending on the status of substrate.

Date of issue:12.08.2017



### **Storage**

- Store in cool, dry place in a well-sealed container away from moist air for 12 months.
- Keep away from heat, ignition sources and from children.

# Caution

- Clean mixing container before use. Do not use dirty tools.
- Do not exceed dilution ratios.
- Keep out of the reach of children

## Health and safety

Possible Hazards: It causes irritation in case of skin contact & eye contact, flush immediately with plenty of water for at least 10 minutes and seek medical advice in case it happened.