

Universal Putty

Product Description

Universal Putty is a high-quality single component, ready-to-use, white acrylic copolymer paste.

Features and benefits

- Easy to apply because of high flexibility.
- Superior adhesion with substrates.
- Excellent hiding power and filling properties to give smooth even surfaces.
- High Coverage.
- Fast drying.

Typical use

- Universal Putty can be used on the interior surfaces of concrete, cement plaster, gypsum board and woodwork.
- It is smooth and easy to apply and gives an ideal surface for subsequent coats.

Substrate

Gypsum Board, Plaster, Cement Board in interior applications.

Product Data

Packaging size	25 Kg, 5 Kg
Form	Paste
Colors	White
Density	1.70 g/m³
Solids by Volume	43 ± 2%
VOC	7 g/l

Date of issue:12.07.2020



Application data

The product can be applied by		
Spatula:	Recommended	
Trowel:	Recommended	
Spray:	Can be used with special airless machines.	

Cleaning of painting tools

Immediate cleaning with water is necessary.

Film Thickness per coat

Dry Film Thickness	100 µm	- 30	00 µm
Theoretical spreading rate	4 m²/Kg	- 1	1.4 m²/Kg

Thinner (solvent to mix with)

Water

Dilution (Mix Ratio)

Universal Putty is ready for use.

Conditions during application

Do not apply if the temperature is below 10°C and not more than 40°C.

Drying and curing time	25 °C
Surface (touch) dry	4 h
Dried/cured for proper sanding	24 h

Directions for use

Surface preparation

Ensure that surface is thoroughly cleaned and free from grease, oil, dirt, salt and other containment.

Date of issue:12.07.2020



Recommended Paint System

Number of coats:

Universal Putty has strong adhesion with concrete surfaces, for superior coverage; apply 2 coats in normal conditions

Storage

- Store in cool, dry place in a well-sealed container away from moist air for 6 months.
- Keep away from heat, ignition sources and from children.

Caution

- Clean mixing container before use. Do not use dirty tools.
- Do not exceed dilution ratios.
- Keep out of the reach of children

Health and safety

Possible Hazards: It causes irritation in case of skin contact & eye contact, flush immediately with plenty of water for at least 10 minutes and seek medical advice in case it happened.