Technical Data Sheet



Unimix TG Plastic

Product Description

Unimix TG Plastic is a special formulated color grout for filling joints between tiles and natural stone installations. Unimix TG Plastic can fill joints up to 5 mm.

Features and benefits

- Smooth appearance
- Uniform UV resisting colors
- Mould-Resistant
- · Variety of colors
- Non toxic

Typical use

- Internal and external applications
- Kitchens
- Bathrooms
- Swimming pools

Product Data

Packaging size 2 Kg, 5 Kg (Plastic Bags)

Form Powder

Colors Different Colors

Solids by volume $98 \pm 2\%$

Slurry density 1.10-1.13 g/cm³

Mixed Density $1.80-1.90 \text{ g/cm}^3$

Pot Life 30-60 minutes at 25°C and 50%RH

Setting Time 24 hours at 25°C and 50%RH

Application data

The product can be applied by

Spatula Recommended

Trowel Recommended

Date of issue:18.11.2023 Page: 1/3



Technical Data Sheet

Cleaning of painting tools

Immediate cleaning with water is necessary.

Film Thickness per coat

Dry film thickness Up to 5 mm

Theoretical spreading rate 4 m²/pack at 5 mm

Thinner (solvent to mix with)

Water

Dilution (Mix Ratio)

Uniguard TG Plastic is provided in powder form, for manual mixing, mixing ration is 0.30 of total weight .Use clean water .

Conditions during application

Do not apply if the temperature is below 5°C and not more than 40°C. For ambient air temperature > 30°C continuous humidification (spraying water mist) is required before and during application. Avoid working under direct sunlight.

Drying and curing time	25 °C
Surface (touch) dry	2 h
Dry to over coat, minimum	2 h
Dried/ cured for proper sanding	24 h

Directions for use

Surface preparation

- Ensure that surface is thoroughly cleaned and free from grease, oil, dirt, salt and other containment.
- Clean the surface with water.

Recommended Paint System

Number of coats:

The thickness of filling to not exceed 5 mm.

Date of issue:18.11.2023 Page: 2/3

Technical Data Sheet



Storage

- Store in cool, dry place in a well-sealed container away from moist air for 6 months.
- Keep away from heat, ignition sources and from children.

Caution

- Clean mixing container before use. Do not use dirty tools.
- Do not exceed dilution ratios.
- · Keep out of the reach of children

Health and safety

Possible Hazards: it causes irritation in case of skin contact & eye contact, flush immediately with plenty of water for at least 10 minutes and seek medical advice in case it happened.

Date of issue:18.11.2023 Page: 3/3