Technical Data Sheet



UMP Tex 02

Product Description

UMP TEX Medium is water based textured exterior paint containing flexible acrylic binder reinforced with tough special fillers. rough textured grain.

Features and benefits

- High weather resistance.
- Good water resistance
- Provides an attractive textured finish.

Typical use

- use on exterior surfaces of cement plaster, concrete and masonry
- used to give attractive decorative finishes on interior substrates Glass Reinforced Concrete (GRC).

Substrate

Concrete, Cement Plaster and Masonry Surfaces.

Product Data

Packaging size 16 Litr

Form Liquid

Colors White

Density 1.70 g/cm³

Solids by volume $45 \pm 2\%$

VOC 12 g/l

Application data

The product can be applied by

Sponge Roller Recommended

Date of issue:18.05.2018 Page: 1/3



Technical Data Sheet

Trowel Recommended

Cleaning of painting tools

Immediate cleaning with water is necessary.

Film Thickness per coat

Dry film thickness 1000 μm - 2000 μm Theoretical spreading rate 0.45 m^2/l - 0.22 m^2/l

Thinner (solvent to mix with)

Water

Dilution (Mix Ratio)

Maximum 10%

Conditions during application

Do not apply if the temperature is below 5°C and not more than 40°C. For ambient air temperature > 30°C continuous humidification (spraying water mist) is required before and during application. Avoid working under direct sunlight.

Drying and curing time 25 °C

Surface (touch) dry 3 h

Dried/ cured 24 h

Directions for use

Surface preparation (Space)

- Ensure that surface is thoroughly cleaned and free from grease, oil, dirt, salt and other containment.
- Clean the surface with water.
- Surface must be dry and fully cured.

Recommended Paint System

Number of coats:

Apply two coats of UMP Tex Medium with GM6 roller.

Storage

- Store in cool, dry place in a well-sealed container away from moist air for 24 months.
- Keep away from heat, ignition sources and from children.

Date of issue:18.05.2018 Page: 2/3





Caution

- Clean mixing container before use. Do not use dirty tools.
- Do not exceed dilution ratios.
- Keep out of the reach of children

Health and safety

Possible Hazards: It causes irritation in case of skin contact & eye contact, flush immediately with plenty of water for at least 10 minutes and seek medical advice in case it happened.

Date of issue:18.05.2018 Page: 3/3