## **Technical Data Sheet**



## **UMP Graffiato**

# **Product Description**

UMP Graffiato is water based textured exterior paint containing flexible acrylic binder reinforced with tough special fillers. Big grain (2mm) for scratched look

#### Features and benefits

- High weather resistance.
- Good water resistance
- Provides an attractive textured finish.

## Typical use

- use on exterior surfaces of cement plaster, concrete and masonry
- used to give attractive decorative finishes on interior substrates Glass Reinforced Concrete (GRC).

#### **Substrate**

Concrete, Cement Plaster and Masonry Surfaces.

## **Product Data**

Packaging size 25 kg

Form Liquid

**Colors** White

**Density** 1.70 g/m<sup>3</sup>

Solids by Volume  $50 \pm 2\%$ 

**VOC** 12.7 g/l

# **Application data**

The product can be applied by

Trowel Recommended

Date of issue:18.05.2018 Page: 1/3



## **Technical Data Sheet**

### Cleaning of painting tools

Immediate cleaning with water is necessary.

#### Film Thickness per coat

Dry film thickness 2 mm

Theoretical spreading rate 0.25 m²/l

### Thinner (solvent to mix with)

Water

#### **Dilution (Mix Ratio)**

Maximum 10%

### **Conditions during application**

Do not apply if the temperature is below 5°C and not more than 40°C. For ambient air temperature > 30°C continuous humidification (spraying water mist) is required before and during application. Avoid working under direct sunlight.

Drying and curing time 25 °C

Surface (touch) dry 3 h

Dry to over coat, minimum 20 h

Dried/ cured 24 h

## **Directions for use**

### **Surface preparation (Space)**

- Ensure that surface is thoroughly cleaned and free from grease, oil, dirt, salt and other containment.
- Clean the surface with water.
- Surface must be dry and fully cured.

#### **Recommended Paint System**

#### Number of coats:

Apply one coat of UMP Graffito with SS trowel, make sure to press the trowel circularly in the substrate to get the desired finish

# **Storage**

- Store in cool, dry place in a well-sealed container away from moist air for 24 months.
- Keep away from heat, ignition sources and from children.

Date of issue:18.05.2018 Page: 2/3





## **Caution**

- Clean mixing container before use. Do not use dirty tools.
- Do not exceed dilution ratios.
- Keep out of the reach of children

# **Health and safety**

Possible Hazards: It causes irritation in case of skin contact & eye contact, flush immediately with plenty of water for at least 10 minutes and seek medical advice in case it happened.

Date of issue:18.05.2018 Page: 3/3