



Uniguard HB Tex

Product Description

Uniguard HB Tex is a high-quality, water-based textured paint that contains flexible acrylic binder reinforced with tough smooth up to rough special fillers. It provides excellent weather resistance and waterproofing properties, protecting surfaces from water ingress while offering a durable, textured finish. Ideal for masonry, concrete, and other exterior surfaces, it enhances both aesthetics and longevity.

Features and benefits

- Waterproofing: Protects surfaces from water penetration and weather damage.
- UV Resistant: Ensures long-lasting color and finish in direct sunlight.
- High Durability: Withstands varying weather conditions, including rain, humidity, and temperature changes.
- Provides an attractive textured finish.
- Easy to apply.

Typical use

- Use on exterior surfaces of cement plaster, concrete and masonry
- Used to give attractive decorative finishes on interior substrates Glass Reinforced Concrete (GRC).

Substrate

- Concrete, Cement Plaster and Masonry Surfaces.

Product Data

Properties	HB Tex Fine	HB Tex Medium	HB Tex Decor
Form	Liquid	Liquid	Liquid
Colors	White	White	White
Solids by Volume	55.40 %	55.10 %	60.00 %
VOC	≤ 0.5 mg/m ³	≤ 0.5 mg/m ³	≤ 0.5 mg/m ³
Density	1.42 g/cm ³	1.43 g/cm ³	1.48 g/cm ³

Application data

The product can be applied by:

HB Tex Fine	Sponge Roller
HB Tex Medium	Sponge Roller, Trowel
HB Tex Decor	Trowel



Cleaning of painting tools

Immediate cleaning with water is necessary.

Film Thickness per coat

	HB Tex Fine	HB Tex Medium	HB Tex Decor
Dry film thickness	350 - 750µm	750 – 1500 µm	750 – 1500 µm
Theoretical spreading rate (m ² /Pack)	28 - 13	13 – 6.5	13.5 – 6.5

Thinner (solvent to mix with)

Water.

Dilution (Mix Ratio)

Maximum 10%.

Conditions during application

Do not apply if the temperature is below 5°C and not more than 40°C. For ambient air temperature > 30°C continuous humidification (spraying water mist) is required before and during application. Avoid working under direct sunlight.

Drying and curing time	25 °C
Surface (touch) dry	2 h
Dried/ cured	24 h

Directions for use

Surface preparation

- Ensure that surface is thoroughly cleaned and free from grease, oil, dirt, salt and other containment.
- Clean the surface with water.
- Surface must be dry and fully cured.

Recommended Paint System

Number of coats:

Apply two coats of HB Tex with recommended tool. Make sure to press the trowel circularly in the substrate to get the desired finish.

Storage

- Store in cool, dry place in a well-sealed container away from moist air for 24 months.
- Keep away from heat, ignition sources and from children.



Caution

- Clean mixing container before use. Do not use dirty tools.
- Do not exceed dilution ratios.
- Keep out of the reach of children.

Health and safety

Possible Hazards: It causes irritation in case of skin contact & eye contact, flush immediately with plenty of water for at least 10 minutes and seek medical advice in case it happened.